

26 35 A VX 6x6

ENGINE

Make Weichai Euro 2 Intercooled Turbo

Model Configuration WP 10-340 E32

Max Power–Kw @ r/min 250/2200

Max Power–N.m @ r/min 1350/1600

HP 350

Cylinder 6 Inline

Water Cooled 🛕 4 Stroke 🛕

Direct Injection

Cylinder Bore & Stroke 126 x 130

Displacement (l) 9.726

Compression Ratio 17:01

Firing Order 1-5-3-6-2-4

BRAKES

Service Dual circuit, full-air drum brakes

Emergency / Parking Spring potential brake
Auxiliary Engine exhaust brake

ABS & EVB Standard

STANDARD TYRE EQUIPMENT

Size and ply rating 14.00-20 Spare Wheel Yes

FRONT AXLE

Type AR7/01DS-7/5.263

Suspension Non-free standing stabilization leaf

spring, hydraulic shock absorber,

transverse stabilizer

REAR AXLE

Type HL7/015DS-13/5.263

Suspension Stabilization suspension, 13pcs leaf

spring (each 20mm) with side stop

plate

ELECTRICAL EQUIPMENT

Alternator 24V, 70Amp
Starter Motor 24V, 5.58kW
Batteries 2 x 12V - 135AH

DIMENSIONS

DIMENSIONS		
Overall Length (OL)	9390	
Overall Width (OW)	2495	
Overall Height (OH)	3275	
Front Overhang (FOH)	1435	
Rear Overhang (ROH)	1940	
Wheel Base (WB)	4450	
Bumper to Back of Cab (BBC)	1846	
Cab to rear axle / unit (CA)	4038	
Turning Circle (TC)	10000/10mt	

PERFORMANCE DATA

Grade Ability @ GVM 60%

Max Geared Road Speed 98km/h

Final Drive Ratio 5.263

CLUTCH

Make / Type / Size GFX 430mm single plate
Operation Single dry frictional disc,
diaphragm spring, pulling type

TRANSMISSION

Make/Model 9T-180 No of Gears 9

Synchromesh or Constant Mesh Synchromesh
Transfer Box LF200

ATIO

KATIU				
Crawler	12.82	7th	1.29	
1st	7.93	8th	1.00	
2nd	6.00	9th	N/A	
3rd	4.43	10th	N/A	
4th	3.43	11th	N/A	
5th	2.31	12th	N/A	
6th	1.75	Revers L	11.21	

CAB

65° Hydraulic Tilt Able Cab

Windscreen Wipers—2 Speed & Intermitted Setting

External Rear View Mirrors

Speedometer / Odometer Ref Counter

Fuel & Engine Temperature Gauges

Air Pressure & Oil Pressure Gauges

Audio & Visual Warning Devices

Air Conditioning & Radio

External Sun Visor

Driver Seat Suspension

MASS INFORMATION

Manufacturers Gross Vehicle Mass (GVM)	26000
Manufacturers Gross Combination Mass (GCM)	43000
Manufacturers Front Axle mass (GA)	7500
Manufacturers Rear Axle mass (GAU)	26000
Permissible Maximum Vehicle Mass (V)	25500
Permissible Maximum Front Axle Mass (AF)	7500
Permissible Maximum Rear Axle Mass (AR)	18000
Unladen Front Axle Mass (UF)	5253
Unladen Rear Axle Mass (UR)	5123
Total Unladen Mass (UT)	10376
Permissible Max Drawing Vehicle Mass (D/T)	43000